

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A maintenance method for an ink jet head which ejects ink supplied via an ink supply path, as ink droplets from a plurality of orifices arranged in an orifice plate, the method comprising:

controlling the pressure in said ink supply path against the atmospheric pressure applied to a surface of the ink to push the ink out of each orifice as a purging operation of ink carried out to remove particles of dirt in the ink and then ~~align~~ maintain the pressure applied to the ink surface of each orifice approximately to the atmospheric pressure such that the surface of the ink to a surface of is not set back from said orifice plate toward said ink supply path after the purging operation; and

sucking ink ~~near each orifice~~ remaining in the vicinity of each orifice and on a surface of said orifice plate surrounding each orifice in a state where ~~the ink surface is approximately aligned to the surface of said orifice plate~~ the pressure applied to the ink surface of each orifice is maintained approximately to the atmospheric pressure.

2. (Currently Amended) A maintenance apparatus for an ink jet head which ejects ink supplied via an ink supply path, as ink droplets from a plurality of orifices arranged in an orifice plate, the apparatus comprising:

a pressure control section which controls the pressure in said ink supply path against the atmospheric pressure applied to a surface of the ink to push ink out of each orifice as a purging operation of ink carried out to remove particles of dirt in the ink and then ~~align~~ maintain the pressure applied to the ink surface of each orifice approximately to the

atmospheric pressure such that the surface of the ink is not set back from to a surface of said orifice plate toward said ink supply path after the purging operation; and

an ink suction section which sucks ink near each orifice remaining in the vicinity of each orifice and on a surface of said orifice plate surrounding each orifice after the purging operation in a state where the ink surface is approximately aligned to the surface of said orifice plate the pressure applied to the ink surface of each orifice is maintained approximately to the atmospheric pressure by said pressure control section.

3. (Original) The maintenance apparatus according to claim 2, wherein said ink suction section includes a suction nozzle which moves in an arrangement direction of said orifices along said orifice plate.

4. (Original) The maintenance apparatus according to claim 3, wherein the surface of said orifice plate is a protection member arranged to surround each orifice, and said suction nozzle is set in contact with or separated from said protection member by an air gap during the movement.

5. (New) The maintenance apparatus according to claim 2, wherein suction of the ink is carried out in a state where the pressure applied to the ink surface is set in a range of between -0.27 kPa and +0.27 kPa.

6. (New) The maintenance apparatus according to claim 5, wherein the pressure applied to the ink surface is set in a range of between -6.7 kPa and -2.0 kPa after suction of the ink is finished.

7. (New) The maintenance method according to claim 1, wherein suction of the ink is carried out in a state where the pressure applied to the ink surface is set in a range of

Application Serial No.: 10/600,434  
Reply to Office Action dated July 29, 2004

between -0.27 kPa and +0.27 kPa.

8. (New) The maintenance method according to claim 7, wherein the pressure applied to the ink surface is set in a range of between -6.7 kPa and -2.0 kPa after suction of the ink is finished.